

Interior work for AUDITORIUM @ Karnataka Agri museum buidling, Agriculture dept, Sheshadri Road, KR CIRCLE BANGLORE						
SR NO.	Description		Unit	Quantity	Rate	Amount
	Technical Specification parameters		value			
	MAKE : SAMSUNG, AERO UNILUMIN(KSLIM), ABS, DELL					
1.00	SUPPLYING AND FIXING LED WALL WITH 2 YEAR WARENTY of size 15'0"x8'0" WITH FRONT AND BACK SERVICE 500X1000 INDOOR DISPLAY UNIT 3.9MM PIXEL PITCH AS PER FOLLOWING REQUIREMENT					
	Pixel Pitch	3.9mm				
	LED Type	3-IN 1 SMD				
	LED Configuration	1 RED 1 BLUE, 1GREEN				
	Brightness	900 CDM SQ				
	Pixels Per Panel	128X256 DOTS				
	Pixel Density	65.536 PXCEL/SQM				
	Weight	13.7kg/panel				
	Module Size	w250mmxH250mmxD18mm				
	Cabinet Size	w500xh250xd60.5mm				
	Aspect Ratio	01:02				
	Area	0.5 sqm				
	Recommended Viewing Distance	>4n				
	Material	Aluminium profile				
	Environment	Indoor				
	Ingress protection	IP40/IP30				
	Operating Temperature/Humidity	10 degree-+45 degree/10-85%RH				
	Storage Temperature/Humidity	20 degree-+55 degree/10-90%RH				
	Maintenance	front and rear	nos	1		
	Gap Between Modules	Seamless				
	Horizontal Viewing Angle	140 degree				
	Vertical Viewing Angle	110 degree				
	Color Temperature	2000-9300K Adjustable				
	Colors	4.4 trillion				
	Brightness Control	Manual/Automatic				
	Calibration	Support Luminance/Chroma				
	Contrast Ratio	3000:01:00				
	Input Power <Max>	250W/Panel				
	Input Power <typ>	82W/panel				
	Driving Method	Constant Current Drive				
	Video Frame Rate	50/60 Hz				
	Rate Refresh	2400 Hz				
	Input Voltage	200~240VAC				
	Input Power Frequency	50~60 Hz				
	Input Signal	DVI/HDMI/VGA/SDI/DP /AV/S-Video, etc				
	LED Life Time	≥100,000 Hours				
	LED Wavelength	R:620~630nm G:520~535nm B:465~475nm				
	Standard Mounting Configuration	Fixed				
	Professional Services	Design, configuration, install and service available				
	Data Interconnection	Network Cable (L≤100m); multi-mode fiber (L≤300m);				
	single mode fiber	(L≤15km)				
	TOTAL AMOUT					